

Excellent spray lubricant

RM Lubrispray is a new generation lubricant for all kinds of mechanisms that can be sprayed from the outside (cables, chains, bearings, hinges, etc.). **RM Lubrispray** is very useful as cutting oil in threading work. Its composition dramatically reduces wear from contact friction between parts and extends the useful life of parts.

- powerful spray lubricant
- anti-wear agents
- due to its high effectiveness and quality, very little is needed
- reduces maintenance costs
- liquid product with no solid particles, for easy penetration
- universal lubricant for general use
- creates a long-lasting protective film that dramatically reduces wear
- contains no adherent components, so parts stay cleaner
- especially designed and useful for lubricating chains, bearings, cables and other mechanisms exposed to harsh weather conditions
- very effective as a cutting oil in threading work
- no solvents

Instructions for use:

Apply directly to parts. Machinery or parts exposed to dust or dirt should be pressure-washed and allowed to dry before re-applying.

Technical characteristics:

Lubricant characteristics	Norm	Value
Colour	Visual	Beige
Aspect	Visual	T and O
Viscosity, cSt at 40° C	ASTM D-445	41,85
Density at 15° C	ASTM D-1298	0,97
Fire point, °C	ASTM D-92	>209
Freezing point, °C	ASTM D-97	<-43
Four-ball test rig (welding load), kg	ASTM-D-2783	>315
Aerosol Characteristics		
Fire point, °C	ASTM D-92	-43
Pressure of contents, bars		3,7

Packaging references:

RM 0010 00400: 400 ml metallic container / aerosol

Recycle containers according to applicable legislation.